



Ceramic Fibre Paper

Technical Characteristics:

- * Low thermal conductivity
- * Low heat storage
- * Excellent electrical & sound insulation
- * Flexible & tear resistant
- * High tensile strength
- * Thermal shock resistance
- * Excellent chemical stability



| | |
|--------------------------------------|--|
| Classification | 1260 |
| Temp °C | |
| Product Name | Ceramic Fibre Paper |
| Density (kg/m3) | 200 |
| Organic Content (%) | ≤ 9 |
| Moisture Content (%) | ≤ 1 |
| Tensile Strength (Mpa) | ≥ 0.3 |
| Shrinkage On Heating (%) | 1000 C X 24h ≤ 3 |
| Standard Size of Products | 1mm x 1220mm (610mm) x 40m 2mm x 1220mm (610mm) x 30m 3mm x 1220mm (610mm) x 20m 4mm x 1220mm (610mm) x 10m 5mm x 1220mm (610mm) x 10m |
| Packaging | Carton |
| Quality & Environment Control System | ISO 9001 - 2000, ISO 14001 - 1996 |

Application Range:

- * High temperature insulating, sealing & protecting material for industry
- * Electrical and thermal insulation for the electrical industry
- * Insulation for instrument equipment
- * Insulating material for the motor industry